



Sizing OF 4-SIDED SPLIT JAMB FOR DOORS:

- A) If all 4-sides are wrapping the wall
 - Door Opening Width = Rough Opening - 1 1/2 "
 - Door Opening Height = Rough Opening - 1 1/2 "
- B) If sill is sitting on floor (Not wrapping)
 - Door Opening Width = Rough Opening - 1 1/2 "
 - Door Opening Height = Rough Opening - 2 3/4 "

SIZING OF 3- SIDED SPLIT JAMB FOR DOORS:

- Door Opening Width = Rough Opening - 1 1/2 "
- Door Opening Height = Rough Opening - 3/4 "

Notes: Adjustability of CUFT0002 is -1/4 and + 3/4 from given jamb width
 For more Adjustability, see CUF0037
 All Sizing Based on 2" Faces, Double Rabbet Profile Only



Karpen Steel
 Custom Doors & Frames
 181 Reems Creek Rd
 Weaverville NC 28787
 www.karpensteel.com

Tel: 828-645-4821
 Fax: 800-851-2131

Revised by: **DSMITH**

Title: **Split Jamb Frames For Doors,
 No Backbend**

Description: **-1/4" + 3/4" Adjustable**

File name: **CUFT0003**

REV

Revision Date: **30APR10**

Sheet